


**KAESER**  
COMPRESSORS



# MOBILAIR Range

Portable compressors with the world-renowned SIGMA PROFILE   
Flow rates 1.2 to 34 m<sup>3</sup>/min

[www.kaeser.com](http://www.kaeser.com)

## Alternative drives – Petrol engine or electric motor

							Alternative electric drive	
Model			M 13	M 15 <sup>*)</sup>	M 17 <sup>*)</sup>	M 17	M 13E	
Flow rate at maximum working pressure	7 bar	m <sup>3</sup> /min	1.2	1.4	1.6	-	1.2	
	100 psi	cfm	42	50	57		42	
	10 bar	m <sup>3</sup> /min	1.0	-	-	-	1.0	
	145 psi	cfm	35				35	
	12 bar	m <sup>3</sup> /min	0.9	-	-	-	0.9	
	175 psi	cfm	32				32	
	13 bar	m <sup>3</sup> /min	0.85	-	-	-	0.85	
	190 psi	cfm	30				30	
15 bar	m <sup>3</sup> /min	-	-	-	1.0	0.75		
215 psi	cfm				35	27		
Engine / motor			Honda GX 630	Honda GX 630	Honda GX 630	Honda GX 630	ABM 4D 112M-2	
Rated motor / engine power		kW	15.5	15.5	15.5	15.5	7.5	
Air treatment			○	○	○	○	○	

\* Only for export outside of the EU



## Compact machines – With the patented Anti-Frost Control

											Alternative electric drive	
Model			M 20	M 27	M 31	M 36	M 43	M 45	M 50	M 34E	M 46E	
Flow rate at maximum working pressure	7 bar	m <sup>3</sup> /min	2.0	2.6	3.15	3.9	4.2	4.2	5.0	3.1	4.4	
	100 psi	cfm	71	92	110	135	150	150	180	110	155	
	10 bar	m <sup>3</sup> /min	-	-	2.6	-	-	4.15	-	-	3.0	
	145 psi	cfm			92			145			105	
	12 bar	m <sup>3</sup> /min	-	-	2.3	-	-	-	-	-	-	
	175 psi	cfm			81							
	14 bar	m <sup>3</sup> /min	-	-	1.9	-	-	-	-	-	-	
200 psi	cfm	67										
Engine			Kubota D722	Kubota D1105	Kubota D1105T	Kubota V2403	Kubota V1505T	Kubota V2203	Kubota V1505T	ATB A160L-21	Siemens 1LA9 183-2	
Rated engine power		kW	14	17.9	24.1	36	30.1	35.4	32.5	22	30	
Air treatment			-	○	○	○	-	○	-	○	○	
Generator option		kVA	-	6.5	6.5	13 (Standard)	-	8.5	-	-	-	




## Exceptional versatility – Wide range of equipment options

									Low emission ZONE	
Model			M 52	M 57	M 57 Utility	M 64	M 70 <sup>*)</sup>	M 58	M 58 Utility	
Flow rate at maximum working pressure	7 bar	m <sup>3</sup> /min	5.2	5.6	5.1 / 5.4 <sup>*)</sup>	6.4	7.0	5.6	5.1 / 5.4 <sup>*)</sup>	
	100 psi	cfm	185	200	180 / 190 <sup>*)</sup>	225	250	200	180 / 190 <sup>*)</sup>	
	10 bar	m <sup>3</sup> /min	-	-	4.35 / 4.7 <sup>*)</sup>	5.0	5.4	4.7	4.35 / 4.7 <sup>*)</sup>	
	145 psi	cfm			155 / 165 <sup>*)</sup>	180	190	165	155 / 165 <sup>*)</sup>	
	12 bar	m <sup>3</sup> /min	-	-	-	-	-	-	-	
	175 psi	cfm								
	14 bar	m <sup>3</sup> /min	-	-	-	-	-	-	-	
200 psi	cfm									
Engine			Kubota V2203	Kubota V2403	Kubota V2403	Kubota V2403T	Kubota V2403T	Kubota V2403-CR	Kubota V2403-CR	
Rated motor power		kW	35.4	36	36	43.3	43.3	36	36	
Air treatment			○	-	○	○	○	○	○	
Generator option		kVA	8.5	-	-	8.5 / 13	-	-	-	



\* Only for export outside of the EU

			Low emission ZONE					
Model			M 100 <sup>1)</sup>	M 122 <sup>1)</sup>	M 81	M 82	M 114	M 115
Flow rate at maximum working pressure	7 bar	m³/min	10.2	11.1	8.4	8.4	-	11.5
	100 psi	cfm	360	390	295	295		405
	8.6 bar	m³/min	-	10.1	-	-	-	10.5
	125 psi	cfm		355				370
	10 bar	m³/min	8.5	9.5	6.8	6.8	9.7	9.7
	145 psi	cfm	300	335	240	240	345	345
	12 bar	m³/min	7.2	8.2	6.1	6.1	8.4	8.4
	175 psi	cfm	255	290	215	215	295	295
	14 bar	m³/min	6.4	7.3	5.5	5.5	7.5	7.5
200 psi	cfm	225	260	195	195	265	265	
Engine			Kubota V3800 Di-T	Deutz TCD 2012 L04	Deutz TD2.9	Kubota V3307-CR-T	Deutz TCD 3.6 L4	Kubota V3800-CRS-TI
Rated motor power		kW	71.7	83	55.4	54.6	85	85
Air treatment			o	o	o	o	o	o
Generator option		kVA	8.5 / 13	-	-	8.5 / 13	-	8.5 / 13



P-295 ED Specifications are subject to change without notice. 2016

\* Only for export outside of the EU

## Large compressors – Savings with SIGMA CONTROL mobile

			Low emission ZONE									
Model			M 123 <sup>1)</sup>	M 135 <sup>1)</sup>	M 170 <sup>1)</sup>	M 200	M 130	M 171	M 250	M 350		
Flow rate at maximum working pressure	7 bar	m³/min	-	-	-	21.2 <sup>1)</sup>	-	-	-	-		
	100 psi	cfm				750 <sup>1)</sup>						
	8.6 bar	m³/min	11.4	-	17.0	19.7	-	17.0	26.3	34.0		
	125psi	cfm	405		600	700		600	930	1200		
	10 bar	m³/min	10.8	13.0	15.5	18.0	12.0	15.5	25.0	31.0		
	145 psi	cfm	380	460	550	640	425	550	885	1095		
	12 bar	m³/min	9.7	12.0	13.5	16.0	10.7	13.5	22.5	27.3		
	175 psi	cfm	345	425	475	565	380	475	795	965		
	14 bar	m³/min	8.1	10.5	11.5	14.5	9.4	11.5	20.0	24.0		
200 psi	cfm	285	370	405	515	330	405	705	850			
Engine			Deutz TCD 2012 L04	Deutz TCD 2013 L04	Deutz TCD 2012 L06	Caterpillar C 6.6	Deutz TCD 4.1 L04	Deutz TCD 6.1 L06	Mercedes Benz OM 926 LA	Mercedes Benz OM 501 LA		
Rated motor power		kW	88	122	128	146	105	129	210 <sup>1)</sup>	215	260 <sup>1)</sup>	265
Air treatment			o	o	o	o	o	o	o	o		
Generator option		kVA	-	23	-	-	23	-	-	-		

\* Only for export outside of the EU